

Product Profile

- Supports industry standard communications
- 2.4 GHz or 802.11b 11 Mbps radio
- Fast and easy integration options for terminal emulation or client/server
- Flexible connectivity choices
- Large, high contrast display
- Rugged casing



Intrinsically Safe model 2425 CS

2 4 2 5 H A N D H E L D C O M P U T E R

The 2425 is the more ruggedized wireless model of the 2400 family hand-held line of data collection terminals. It is a cost-effective and reliable solution for collecting data in manufacturing, distribution and warehouse environments. An Intrinsically Safe model provides protection in hazardous areas containing gas, vapors and dust.

For fast and easy implementation, the 2425 integrates with common host environments using standard protocols. Configure the 2425 with TCP/IP for a direct connection to your Ethernet or

Token Ring LAN or connect to Ethernet and IBM networks through the DCS 300 Server, which also provides guaranteed host connection and network management services.

With a contoured shape and centered scan button, the 2425 is comfortable to use in either hand. The large display provides enough space for menus, help screens or even graphics. It is tilted to improve readability while scanning, and the alphanumeric keyboard provides tactile feedback with the frequently used numeric keys oversized for easier input.

Physical Characteristics

Length: 26.9 cm (10.6")
Height: 7.1 cm (2.8") at scanner, 5.7 cm (2.3") at grip
Width: 8.2 cm (3.2") at scanner, 6.4 cm (2.5") at grip
Weight: 766 g (27 oz.) including battery

Environment

Operating: -20° to 50°C (-4° to 122°F)
Storage: -20° to 60°C (-4° to 140°F) for less than two weeks
Humidity: Non-condensing (0 to 95% RH)
Shock and Vibration Protection: Warranted for 5-foot drop to concrete Meets MIL-STD 28800E

Power

Operating: Lithium Ion battery pack
Memory Backup: Rechargeable NiCad

Memory

RAM Memory: 1MB
Non-volatile Flash Memory: 2MB
 Option for 2MB additional, 4 MB total

Interfaces

- Optical Serial Interface
- RS232-C up to 38.4 baud
- XMODEM, YMODEM for data transfer
- Supports Configurable Serial Protocol and XON/OFF

Display

- CGA compatible backlit LCD displaying 16 lines of 20 characters per line (160 x 128 dot matrix) plus graphic status icons
- Full 25 x 80 virtual screen with viewporting

Keyboard

- Elastomeric 56-key with full alphanumeric set, function keys and oversized numeric
- Options for U.S., Multilingual European, IBM 5250, IBM 3270 and VT/ANSI layouts

**Software**

Programmable: Microsoft® C
Terminal Emulation: IBM 3270 and 5250 SNA and TELNET; ANSI/VT 100, 220, 320 TELNET; Screen mapping
Web-based: dcBrowser™ for HTML applica-tions

Connectivity

- Direct TCP/IP Support
- DHCP Client
- Sockets interface or terminal emulation
- Ethernet or Token Ring

Bar Code Symbolgies

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN Code 128, Code 11, Code 93, Plessey, MSI, Code, PDF-417

Bar Code Scanning Options

Integrated visible laser diode scanner
 USA/Canada Class II, International Class 2
Depth of Field*--Standard Range (670nm)

5 mil	9.4-15.7cm	3.7-6.2"
10 mil	7.4-35.3cm	2.9-13.9"
20 mil	10.2-63.5cm	4-25"
30 mil	10.2-86.4cm	4-34"
40 mil	12.7-99cm	5-39"
55 mil	19.1-126cm	7.5-49"
55 mil retroreflective	105-151cm	41-59"
100 mil retroreflective	113-227cm	44-89"

Depth of Field*--Long Range (650nm)

5 mil	29.5-49.8cm	11.6-19.6"
10 mil	21.8-85.3cm	8.6-33.6"
20 mil	21.8-98cm	8.6-38.6"
30 mil	24.4-192cm	9.6-75.6"
40 mil	24.4-204.7cm	9.6-80.6"
70 mil retroreflective	192-410.5cm	76.6-161.6"
100 mil retroreflective	212.3-532.4cm	83.6-209.6"

*Measured for Code 39

- High Density and High Performance option available
- Optional adapter module for use with cabled scanners and wands

Integrated RF Module

Frequency: 2.4 GHz frequency band, actual frequencies in use vary by country
WLI Forum OpenAir
Type: Frequency Hopping Spread Spectrum
Data Rate: 1.6 Mbps, .8 Mbps fallback
Range*: From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment

IEEE 802.11b Wi-Fi Certified

Type: Direct Sequence Spread Spectrum
Data Rate: 11/5.5/2/1 Mbps with Auto fallback for increased range
Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment
Range* at 11 Mbps: From 525 ft (160 m) to 80 ft (24 m) depending on environment
Security: Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption
 *Unlimited range with roaming

Host Support via DCS 300 Server

Host Environment: IBM AS 400, S/390, Digital, HP, UNIX, Windows NT
Connectivity: Ethernet, Token Ring, 100BASET, Twinax, Coax, SDLC
 Communications: TCP/IP, SNA

Accessories

Handstrap, holster, belt clip, pistol grip handle, vehicle mount holder, battery charger, battery pack, serial adapter and communications dock, User manuals, Programmer's Software Kit (PSK), EZBuilder™ Rapid Application Development software

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TÜV Rheinland GS, EN 60950 and EN 60825-1, FCC Part 15, Canada, RSS210 and ICES-300 Class B, EN 55022 / CISPR 22, Class B, ETS 300 328, ETS 300 826, Compliant with all European directives, CE marked

Intrinsically Safe Model 2425CS

Please contact your Intermec representative for configurations available

Regulatory Approvals

UL Listed, UL 913 and C22.2 No. 157 Division 1: Class I - Groups C&D
 SIRA Certified to CENELEC EN 50020, rated E EX (ia) IIB T4

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

