

VEHICLE-MOUNT/STATIONARY COMPUTERIntermec® **5055****Benefits:**

- **Open systems**
- **Faster implementation and support**
- **Compact, rugged design**
- **Investment protection through modular design**
- **Lower overall lifetime cost of ownership**
- **Wireless LAN connectivity with WiFi certified 2.4 GHz 802.11b (11Mbps) and OpenAir**
- **Wireless scanning**

The rugged Intermec 5055 vehicle mount and stationary computer is designed for data collection applications in warehousing and distribution, manufacturing, transportation, and customer service. The 5055 is engineered to make data collection a seamless part of the enterprise with your choice of operating systems, currently including Microsoft® Windows® NT, Windows® 95 and MS-DOS®.

State of the art development tools, such as Visual C++, Visual Basic, Java, and HTML, can be used with the 5055. An accessible hard drive and two PC card slots provide investment protection by making upgrades, service and support fast and easy.

The 5055 modular design allows efficient operations and support by allowing convenient swap-out of radios and hard drives, permitting on-site personnel to upgrade hardware.

Touch screen graphics and capabilities allow visual presentation of data and work direction while easy-to-use symbols and icons help navigate applications.

The 5055's space-saving housing allows convenient mounting to material handling equipment, trucks, manufacturing stations, and between dock doors. With a hardened, lightweight magnesium housing, the 5055 is resistant to shock, vibration and unstable power environments.



The 5055 was designed with capability in mind. The 5055 supports both 802.11b 11Mbps and OpenAir for wireless connection to your network. It supports Intermec's own wireless scanning system. The system can avoid inadvertent shutdowns and power loss with an uninterruptable power supply (UPS) on material handling vehicle. A unique recovery disk drive partition allows customers to re-image or recover corrupt drives.

Intermec® 5055

Physical Characteristics**Height:** 23.5 cm (9.3")**Width:** 30.5 cm (12")**Depth:** 5.5 cm-top (2.18")
9.4 cm-bottom (3.72")**Weight:** 3.2-4.0 kg depending on configuration (lightweight, durable magnesium enclosure)**Display****Viewing Area:** 26.4 cm (10.4")**Options:** Color Active Matrix TFT**VGA:** 640x480 pixels**SVGA:** 800x600 pixels**User Interface**

High resolution, resistive touch panel

Environment**Operating Temperature:** -30° to 50° C (-22° to 122° F)**Storage Temperature:** -35° to 70° C (-31° to 158° F)**Humidity:** 0% to 95% non-condensing**Shock Vibration Protection:** Withstands standard material handling vehicle environments**Rain and Dust:** Sealed to IP54**Power**

Choice of two external DC/DC converters

6-36V DC for 12V systems (gas trucks)

15-96V DC for 24-72V systems (electric trucks)

AC/DC Converter

Uninterruptable power supply (UPS) for DC voltage

Processor

AMD 333 MHz

Memory

64, 128MB Options

16MB on-board solid state FLASH

2MB Video RAM

Operating Systems

Windows 95 (OEM) OSR2

Windows NT 4.0

MS-DOS 6.22

Hard Drives

Solid state San Disk options for rugged, vehicle based applications

Spinning hard disk option for stationary applications

RF Options

802.11b 2.4GHz (Direct Sequence Spread Spectrum)

100mW max output power

802.11b standard

100mW max output power

Data Speed: 11 Mbps**Coverage:** > 80 m

OpenAir 2.4GHz (Frequency Hopping Spread Spectrum)

100mW max output power

Data Speed: 1.6 Mbps**Coverage:** >80 m**Antenna Options:**

Omni-directional on unit

Remote patch antenna

Network Connectivity

10BaseT Ethernet on-board

Application Connectivity

Supports terminal emulation applications with MS-DOS 6.22 operating system

Supports standard Windows environment application development and connectivity

Interfaces

2 Serial ports supporting serial bar-code scanners

1 enhanced parallel port

1 speaker/headset jack

1 microphone jack

1 PS/2 Keyboard connector (accepts locking standard PS/2 connectors)

1 Mouse connector

Power connector

On/Off switch

Accessible Expansion Slots

One 6.4 cm (2.5") IDE drive bay

Two Type II/Type III PC card slots

PC Sound System

Dual speakers

Speaker/Headset jack supports external speaker sound system

SoundBlaster & Windows sound compatible

Microphone jack

Regulatory Approvals**EMC:**FCC Part 15/ICES-003/CISPR 22 Class B, EMC Directive 89/336/EEC (CE Marked), ETS 300 826, AS 3548 (C-Tick Marked)**Safety:**UL Listed - UL 1950/CSA 22.2, No. 950; Low Voltage Directive 72/32/EEC (IEC 950); NYCE NOM 19 Certified**Radio Options:** FCC, Industry Canada, SCT Approved, ETSI, R&TTE Directive compliant**Accessories**

- Mounting kit
- Desktop adapter plate
- Optional rugged keyboards for DOS/PC
- VT220, 5250, 3270, and Native emulation
- Recovery/re-imaging CD-ROM

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

Internet • www.intermec.com **Sales** • 800.347.2636 (toll free in N.A.), 425.348.2726 **Service and Support** • 800.755.5505 (toll free in N.A.), 425.356.1799**North America**
Corporate Headquarters • 6001 36th Avenue West, Everett, Washington 98203, tel: 425.348.2600, fax: 425.355.9551
Systems & Solutions • 550 2nd Street S.E., Cedar Rapids, Iowa 52401, tel: 319.369.3100, fax: 319.369.3453
Media Supplies • 9290 Le Saint Drive, Fairfield, Ohio 45014, tel: 513.874.5882, fax: 513.874.8487**Europe/Middle East & Africa**
Headquarters • Sovereign House, Vastern Road, Reading, Berkshire RG1 8BT, United Kingdom, tel: +44.118.987.9400, fax: +44.118.987.9401
Gothenburg • Idrottsvägen 10, P.O. Box 123, SE-431 22 Mölndal, Sweden, tel: +46.31.869500, fax: +46.31.869595**Asian Pacific/Latin America**
Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong, tel: 852.2574.9777, fax: 852.2574.9725
Singapore • 25-16 International Plaza, 10 Anson Road, 079903, tel: 65.324.8391, fax: 65.324.8393
Australia • 15 Stamford Road, Oakleigh, Victoria 3166, tel: 61.3.9563.0000, fax: 61.3.9563.4000
South America and Mexico • 2572 White Road, Irvine, California 92614, tel: 949.975.1905, fax: 949.975.1913**Worldwide Fax Document Retrieval Service** • 800.755.5505 (North America Only) • tel: 650.556.8447

Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their owners. Printed in the U.S.A. 608852-01B 11/00

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal.ch • **OPAL Associates SA** • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opalsa.ch • **Germany** • OPAL Associates GmbH • Lohnerhofstr. 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opalgmbh.de • **OPAL Associates GmbH** • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email hamburg@opalgmbh.de • **Austria** • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opalgmbh.at

